




PROPERTIES	STANDARDS	DROPZONE SPECKLE
DECLARATION OF PERFORMANCE		
0120-087DoP-2022-04		
CLASSIFICATION		
Type of floor covering	EN 1817	Homogeneous rubber floorcoverings
TECHNICAL CHARACTERISTICS		
Total thickness	ISO 24346 (EN 428)	8mm (± 0.2 mm)
Total weight	ISO 23997 (EN 430)	8.4 kg/m ²
Width	ISO 24341 (EN 426)	1500mm (± 0.8 %)
Length	ISO 24341 (EN 426)	15m (± 0.8 %)
TECHNICAL PERFORMANCES		
Shock absorption	EN 14808	13%
Ball rebound	EN 12235	100%
Residual Indentation	EN 24343-1	0.14mm
Reaction to fire	EN 13501-1	Efl*
Tensile strength	EN ISO 1798	1.5 N/mm ²
Elongation at break	EN ISO 1798	80%
Hardness	DIN 53505	60 ± 5 Shore A
Temperature range	Internal testing	-30°C to 80°C
Abrasion	DIN 53516	max. 200 mm ³
Coefficient of friction	EN13893	> 0.3 μ (DS)
Reduction of impact noise	EN ISO 717-2	18dB
Thermal resistance	EN ISO 10456	Approx. 0.05 m ² K/W <i>compatible with underfloor heating</i>

AVAILABLE COLOURS



* On concrete and screed



Installation and maintenance guides available on [Tarkett Sports Indoor website](https://en.tarkett.com)

Technical data in force as from the date of publication (03/2024). The values above correspond to laboratory test (no in situ test) and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett Sports. Colours of the products shown in the photos or samples are indicative only. There may be differences in colour, gloss and embossing structure between the products sold and photos or samples.

<https://en.tarkett.com>