

# DROPTILE BLACK

## Technical data



PROPERTIES	STANDARDS	DROPTILE BLACK
------------	-----------	----------------

### DECLARATION OF PERFORMANCE

0120-089DoP-2022-12

### CLASSIFICATION

Type of floor covering	-	Rubber indoor floorcoverings
------------------------	---	------------------------------

### TECHNICAL CHARACTERISTICS

Total thickness	ISO 24346 (EN 428)	30mm (± 2 mm)
Total weight	ISO 23997 (EN 430)	27kg/m <sup>2</sup>
Unit weight	ISO 23997 (EN 430)	13.5kg
Width	ISO 24341 (EN 426)	500mm (± 0.8 %)
Length	ISO 24341 (EN 426)	1000mm (± 0.8 %)

### TECHNICAL PERFORMANCES

Shock absorption	EN 14808	51%
Ball rebound	EN 12235	98%
Reaction to fire	EN 13501-1	Cfl-s1*
Tensile strength	EN ISO 1798	0.75N/mm <sup>2</sup>
Elongation at break	EN ISO 1798	50%
Hardness	DIN 53505	60 ± 5 Shore A
Temperature range	Internal testing	-30°C to 80°C
Friction	EN13036-4	80-110
Coefficient of friction	EN13893	> 0.3 μ (DS)
Reduction of impact noise	EN ISO 717-2	26dB

\* On concrete and screed

Installation and maintenance guides available on [Tarkett Sports Indoor website](https://en.tarkett.com)



Technical data in force as from the date of publication (03/2024). The values above correspond to laboratory test (no in situ test) and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett Sports. Colours of the products shown in the photos or samples are indicative only. There may be differences in colour, gloss and embossing structure between the products sold and photos or samples.

<https://en.tarkettsportsindoor.com/>