

DROPTILE SPECKLE

Technical data



| PROPERTIES | STANDARDS | DROPTILE SPECKLE |
|------------|-----------|------------------|
|------------|-----------|------------------|

| DECLARATION OF PERFORMANCE | | |
|----------------------------|--|--|
|----------------------------|--|--|

0120-090DoP-2022-12

| CLASSIFICATION | | |
|----------------|--|--|
|----------------|--|--|

| | | |
|------------------------|---|------------------------------|
| Type of floor covering | - | Rubber indoor floorcoverings |
|------------------------|---|------------------------------|

| TECHNICAL CHARACTERISTICS | | |
|---------------------------|--|--|
|---------------------------|--|--|

| | | |
|-----------------|--------------------|---------------------|
| Total thickness | ISO 24346 (EN 428) | 30mm (± 2 mm) |
| Total weight | ISO 23997 (EN 430) | 27kg/m ² |
| Unit weight | ISO 23997 (EN 430) | 13.5kg |
| Width | ISO 24341 (EN 426) | 500mm (± 0.8 %) |
| Length | ISO 24341 (EN 426) | 1000mm (± 0.8 %) |

| TECHNICAL PERFORMANCES | | |
|------------------------|--|--|
|------------------------|--|--|

| | | |
|---------------------------|------------------|--------------------------|
| Shock absorption | EN 14808 | 45% |
| Ball rebound | EN 12235 | 95% |
| Reaction to fire | EN 13501-1 | Cfl-s1* |
| Tensile strength | EN ISO 1798 | 0.7N/mm ² |
| Elongation at break | EN ISO 1798 | 70% |
| Hardness | DIN 53505 | 60 ± 5 Shore A |
| Temperature range | Internal testing | -30°C to 80°C |
| Abrasion | DIN 53516 | max. 450 mm ³ |
| Coefficient of friction | EN13893 | > 0.3 μ (DS) |
| Friction | EN13036-4 | 80 - 110 |
| Reduction of impact noise | EN ISO 717-2 | 24dB |

* On concrete and screed



Installation and maintenance guides available on Tarkett Sports Indoor website

Technical data in force as from the date of publication (03/2024). The values above correspond to laboratory test (no in situ test) and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett Sports. Colours of the products shown in the photos or samples are indicative only. There may be differences in colour, gloss and embossing structure between the products sold and photos or samples.