



PROPERTIES	STANDARDS	DROPZONE COMFORT
------------	-----------	------------------

DECLARATION OF PERFORMANCE

0120-084DoP-2022-12

CLASSIFICATION

Type of floor covering	-	Homogeneous rubber floorcoverings
------------------------	---	-----------------------------------

TECHNICAL CHARACTERISTICS

Total thickness	ISO 24346 (EN 428)	8mm (± 0.6 mm)
Total weight	ISO 23997 (EN 430)	8.6 kg/m ²
Width	ISO 24341 (EN 426)	1250mm (± 0.8 %)
Length	ISO 24341 (EN 426)	15m (± 0.8 %)

TECHNICAL PERFORMANCES

Shock absorption	EN 14808	20%
Ball rebound	EN 14877	100%
Reaction to fire	EN 13501-1	Cfl-s1*
Tensile strength	EN ISO 1798	min. 0.7 N/mm ²
Elongation at break	EN ISO 1798	min. 70%
Hardness	DIN 53505	60 ± 5 Shore A
Temperature range	Internal testing	-30°C - 80°C
Abrasion	DIN 53516	max. 450 mm ³
Coefficient of friction	EN13893	> 0.3 μ (DS)
Slip resistance	DIN 51130	R10
Electrostatic properties	EN1815	<2kV
Reduction of impact noise	EN ISO 717-2	18dB
Thermal resistance	EN ISO 10456	Approx. 0.038 m ² K/W <i>compatible with underfloor heating</i>

* On concrete and screed

Installation and maintenance guides available on [Tarkett Sports Indoor website](https://en.tarkettsportsindoor.com/)



Technical data in force as from the date of publication (03/2024). The values above correspond to laboratory test (no in situ test) and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett Sports. Colours of the products shown in the photos or samples are indicative only. There may be differences in colour, gloss and embossing structure between the products sold and photos or samples.